



## SUPREME C3-X SYNTHETIC 5W-30 MULTIGRADE MOTOR OIL

### Introduction

**SUPREME C3-X Synthetic** motor oil is designed to lubricate high-performance gasoline and light duty diesel engines for today's passenger cars, sport utility vehicles, vans and light duty trucks.

**SUPREME C3-X Synthetic** is a top quality "Mid SAPS"\* passenger car motor oil that delivers outstanding performance and protection when lubricating today's modern engines. Promoting balanced lubrication, demonstrated through rigorous testing, it is specially formulated with a combination of synthetic base oils and advanced additive chemistry to exceed the demands of both the industry and European OEMs. This premium motor oil is specifically designed to protect both gasoline catalytic converters and diesel particulate filters, to deliver excellent fuel economy performance and to provide outstanding wear protection and deposits control under the most severe driving conditions.

**SUPREME C3-X Synthetic** delivers exceptional resistance to thermal breakdown, outstanding low temperature fluidity and excellent engine protection at extreme operating temperatures.

**SUPREME C3-X Synthetic** meets ACEA C3 and API SN. The formulation is approved against VW 504 00 / 507 00†, MB 229.51†, Porsche C30† and BMW LL-04†.

### Features and Benefits

- **Extended Engine Life**
  - Superior oil film stability
  - Outstanding protection against wear, rust and corrosion
  - Bearing life greatly extended
  - Excellent wear protection on rings, liners and camshafts
  - Minimizes corrosion due to stop-start driving in cold weather
  - Suitable seal compatibility to prevent leaks
- **Resistance to High Temperature Thermal Breakdown**
  - Cleaner running engines
  - Reduces deposits of varnish, sludge and carbon on engine parts
  - Protects turbochargers from deposit formation
  - Prevents piston-ring sticking
  - Minimizes piston deposits

- **Outstanding Fuel Economy Performance**
  - Exceeds the ACEA C3 requirements for fuel economy performance
- **Protection of Emission System**
  - Selected Phosphorus and Sulphur additive technology that will protect the after-treatment device in gasoline engines and the appropriate Ash Content to protect diesel particulate filters (DPFs).
- **Excellent Low Temperature Fluidity**
  - Permits easier unaided cold weather starts
  - Reduces wear during low temperature start-up and operation
- **Reduced Oil Consumption**
  - Ultra low evaporation loss results in less oil top-up
- **Extended Drain Capability**
  - Allows for flexible oil drain intervals managed by the vehicles on-board computer
- **Compatible with High Ethanol Fuels (up to E85)**
  - Protects against engine corrosion
  - Prevents water separation

### Applications

**SUPREME C3-X Synthetic 5W-30** motor oil is recommended for current passenger cars, vans, sport utility vehicles and light duty trucks powered by gasoline or diesel engines.

**SUPREME C3-X Synthetic 5W-30:** ACEA C3, API SN, VW 504 00/507 00†, MB 229.51†, Porsche C30†, BMW LL-04†

Always consult the owner's manual to select the appropriate viscosity grade for the vehicle.

### Product Availability

**SUPREME C3-X Synthetic 5W-30** motor oil is available globally. It is available for bulk orders in certain regions. Check with your sales representative for details.

## Typical Performance Data

PROPERTY	TEST METHOD	SUPREME C3-X SYNTHETIC 5W-30
Density, kg/L @ 15°C / 60°F	D4052	0.851
Colour	D1500	<2.5
Flash Point, COC, °C / °F	D92	229 / 444
Pour Point, COC, °C / °F	D5950	-45 / -49
Kinematic Viscosity cSt or mm <sup>2</sup> /s @ 40°C cSt or mm <sup>2</sup> /s @ 100°C	D445	66.4 11.7
Viscosity Index	D2270	172
Cold Cranking Viscosity, cP or mPa.s @ °C / °F	D5293	5900 @ -30 / -22
Borderline Pumping Viscosity, cP or mPa.s @ °C / °F	D4684	16400 @ -35 / -31
Volatility (Noack), % loss	D5800	9.0
Sulfated Ash, % wt.	D874	0.8
Sulfur, mass %	D4294	0.192
Phosphorus, mass %	D4951	0.078
Base Number, (BN), mg KOH/g	D2896	7.8
High-Temperature High-Shear (HTHS) Viscosity, cP or mPa.s @ 150°C, 10 <sup>6</sup> s <sup>-1</sup>	D4683	3.5

The values quoted above are typical of normal production. They do not constitute a specification.

To order product or to learn more about how Petro-Canada Lubricants can help your business visit: [lubricants.petro-canada.com](http://lubricants.petro-canada.com) or contact us at: [lubecsr@petrocanadalsp.com](mailto:lubecsr@petrocanadalsp.com)



IM-8134E (2018.11)

™ Owned or used under license.

Beyond today's standards.™

